



Decorative Films

Innovation in graphic films.

Recommended Application Methods for Optimal Performance

Applying Vinyl Film:

- Optimal temperature for the application of our films is 70 degrees F.
- Pressure sensitive vinyls may resist sticking immediately to very cold surfaces.
- Do not apply wet. The warranty is voided for wet applications.
- Apply only to clean smooth non-porous surfaces.

Preventing Edge Curl:

- Cut a ¼" border around images printed with solvent or ecosolvent.
- Edge sealing is recommended – using a fine-tip brush paint the edges of the film with a commercial grade product.

Durability:

- Outdoor durability will vary depending on finishing and exterior conditions. Use of a UV protective clear coat or over laminate film will extend the outdoor durability.
- Current rating is 5 years pending on environment.

Plotter Cutting:

- Use a sharp 45 degree blade at slow cutting speeds with swivel type of cutters. Optimal cutting pressures vary depending on plotter type and blade sharpness. Typical pressure is between 135 grams and 165 grams. Never cut into the printed image.

Printability

- Most printing techniques do not require any surface treatment including screen printing, Ecosolve ink jet, latex and UV curable ink, thermal transfer, hot foil stamping, applying other PS adhesives, flexo printing and offset printing are routinely conducted on Griff products as supplied. Water based ink jet is not recommended at this time. As always, it is suggested the decorating technique be tested for suitability.

Check out our website for updates on the company and our products.

gdf.thegriffnetwork.com

700 Vassar Ave.
Lakewood, NJ 08701, USA
Phone: (732) 367-6203
E-mail: sales@tapeandlabel.com